

80116

08.10.2007	Raw Material - Specification		page 1
Raw Material Name : LA002ST : SD Alcohol 40B 200PF	Structure 1	Date of Filling Index 19.07.2007 B	

Method	Sensory Evaluation		Acceptable Values
	Appearance Color Odor	liquid colorless mild	according standard according standard according standard

Method	Physical / chemical Evaluation	Acceptable Values
	Color, Pt-Co units specific gravity [60°F] Ethyl Alcohol [%] (w/v) Water content [%] (w/v) tert-butyl Alcohol [%] (w/v) Acidity (as acetic acid) [g/100ml] Denatonium benzoate [%] (w/v)	<= 10,0 0,7934 - 0,7946 99,62 - 99,88 <= 0,13 0,1100 - 0,1300 <= 0,0014 0,0005 - 0,0007

CTFA/INCI: ALCOHOL DENAT.		
Supplier: ASHLAND DISTRIBUTION COMPANY FAIRF	Manufacturer: Grain Processing Corp.	Tradename: SD Alcohol 40B 200PF
microbiological check:	No max.	[CFU/g]
Remarks:	With handing over the new specification all previous specifications are losing their validity	
Remarks Purchase		

Safety Data Sheet
Ethanol SDA 40B 200 Proof

Version 1.5

Revision Date: 03/02/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Ethanol SDA 40B 200 Proof

Recommended use of the chemical and restrictions on use

Recommended use : Industrial chemical

Manufacturer or supplier's details

Company : Nexeo Solutions, LLC.
Address : 3 Waterway Square Place Suite 1000
The Woodlands, TX. 77380
United States of America

Emergency telephone number:

Health North America: 1-855-NEXEO4U (1-855-639-3648)

Health International: 1-855-NEXEO4U (1-855-639-3648)

Transport North America: CHEMTREC (1-800-424-9300)

Additional Information: : Responsible Party: Product Safety Group
E-Mail: msds@nexeosolutions.com
SDS Requests: 1-855-429-2661
SDS Requests Fax: 1-281-500-2370
Website: www.nexeosolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.
No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.

Safety Data Sheet
Ethanol SDA 40B 200 Proof

Version 1.5

Revision Date: 03/02/2017

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

CAS-No.	Chemical Name	Weight %
64-17-5	Ethanol	90 - 100

Any Concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.

Safety Data Sheet
Ethanol SDA 40B 200 Proof

Version 1.5

Revision Date: 03/02/2017

- | | | |
|-------------------------|---|---|
| In case of skin contact | : | If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : | Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : | Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |

SECTION 5. FIREFIGHTING MEASURES

- | | | |
|---|---|---|
| Suitable extinguishing media | : | Alcohol-resistant foam
Carbon dioxide (CO2)
Dry chemical |
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during fire-fighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | No hazardous combustion products are known |
| Specific extinguishing methods | : | Use a water spray to cool fully closed containers. |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments. |
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions | : | Prevent product from entering drains. |

Safety Data Sheet
Ethanol SDA 40B 200 Proof

Version 1.5

Revision Date: 03/02/2017

Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation hood. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
64-17-5	Ethanol	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0

Safety Data Sheet
Ethanol SDA 40B 200 Proof

Version 1.5

Revision Date: 03/02/2017

	STEL	1,000 ppm	ACGIH
--	------	-----------	-------

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless

Odour : sweet, alcohol-like

Odour Threshold : No data available

pH : No data available

Freezing Point (Melting point/range) : -114.1 °C (-173.4 °F)

Boiling Point (Boiling point/boiling range) : 78.5 °C (173.3 °F)

Flash point : 13 - 16 °C (55 - 61 °F)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 19 %(V)

Lower explosion limit : 3.3 %(V)

Vapour pressure : 44.59 mmHg @ 20 °C (68 °F)

Relative vapour density : 1.6(Air = 1.0)

Safety Data Sheet
Ethanol SDA 40B 200 Proof

Version 1.5

Revision Date: 03/02/2017

Relative density	: 0.789 @ 20 °C (68 °F) Reference substance: (water = 1)
Density	: 0.789 g/cm ³ @ 20 °C (68 °F)
Solubility(ies) Water solubility	: completely soluble
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: 363 °C
Thermal decomposition	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reac- tions	: No hazards to be specially mentioned.
Conditions to avoid	: Extremes of temperature and direct sunlight. Heat, flames and sparks.
Incompatible materials	: Alkali metals Ammonia Oxidizing agents peroxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Serious eye damage/eye irritation

Components:

64-17-5:

Safety Data Sheet
Ethanol SDA 40B 200 Proof

Version 1.5

Revision Date: 03/02/2017

Species: Rabbit
Result: Irritating to eyes.

Carcinogenicity

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Ozone Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Safety Data Sheet
Ethanol SDA 40B 200 Proof

Version 1.5

Revision Date: 03/02/2017

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact NEXEO's Environmental Services Group at 800-637-7922.

Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):
UN1170, ETHANOL, 3, II

IATA (International Air Transport Association):
UN1170, ETHANOL, 3, II

IMDG (International Maritime Dangerous Goods):
UN1170, ETHANOL, 3, II, Flash Point: 13 - 16 °C(55 - 61 °F)

SECTION 15. REGULATORY INFORMATION

WHMIS Classification : B2: Flammable liquid
D2B: Toxic Material Causing Other Toxic Effects

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Acetaldehyde	75-07-0	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Safety Data Sheet
Ethanol SDA 40B 200 Proof

Version 1.5

Revision Date: 03/02/2017

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
Immediate (Acute) Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

75-07-0 Acetaldehyde

The following chemical(s) are listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F):

75-07-0 Acetaldehyde

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

64-17-5 Ethanol
75-07-0 Acetaldehyde
75-65-0 Tert-butyl alcohol
67-63-0 Isopropyl alcohol

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

75-07-0 Acetaldehyde

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

75-07-0 Acetaldehyde

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

US State Regulations

Massachusetts Right To Know

64-17-5	Ethanol	90 - 100 %
75-07-0	Acetaldehyde	0 - 0.1 %

Pennsylvania Right To Know

64-17-5	Ethanol	90 - 100 %
75-07-0	Acetaldehyde	0 - 0.1 %
75-65-0	Tert-butyl alcohol	0 - 0.1 %

New Jersey Right To Know

64-17-5	Ethanol	90 - 100 %
---------	---------	------------

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.
75-07-0 Acetaldehyde

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

Safety Data Sheet
Ethanol SDA 40B 200 Proof


Version 1.5

Revision Date: 03/02/2017

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 03/02/2017

Legacy SDS: : R0190894

Material number:

16118594, 16118593, 16063702, 743550, 724863, 715066, 542250, 122437, 160380, 161164, 146618, 160120, 161048, 81421, 81761, 115214, 99399

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals

Safety Data Sheet
Ethanol SDA 40B 200 Proof

Version 1.5

Revision Date: 03/02/2017

EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		